


Super Fast Surface Mount Rectifiers
SOD-123FL(eSGA)

Features

- ROHS compliant
- Glass passivated chip
- High forward surge capability
- Meet MSL level 1, per J-STD-020 LF maximum peak of 250 °C
- Solder dip 260 °C / 40S
- Component in accordance to ROHS 2002/95/EC and WEEE 2002/96/WC
- UL recognition, file number E342874


Primary characteristics

$I_{F(AV)}$	1A
V_{RRM}	50V to 600V
I_{FSM}	30A
I_{RM}	5uA
V_{FM} at $I_F=1A$	0.95/1.3/1.7V
T_J max.	150 °C

Applications

Ideal for ac-to-dc bridge full wave rectification such as SMPS, home appliances, office equipment, industrial automation applications

Mechanical data

- SOD-123FL(eSGA)
- Epoxy meets UL 94 V-0 flammability rating
- Terminals: Tin plated leads.
- Polarity: As marked.
- Mounting Torque:10cm·kg(8.8 inches·lbs)max.
- Recommended Torque:5.7 cm·kg(5 inches·lbs)

Maximum rating (Ta=25°C unless otherwise noted)

Parameter	Sym	SOD-123FL(eSGA)					Unit
		FU1	FU2	FU3	FU4	FU5	
Max. repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	V
Max. RMS reverse voltage	V_{RMS}	35	70	140	280	420	V
Max. DC blocking voltage	V_{DC}	50	100	200	400	600	V
Max. average forward current	$I_{F(AV)}$	1					A
Non-repetitive peak forward surge current 8.3ms single half-sine-wave	I_{FSM}	30					A
Max. instantaneous forward voltage drop per diode	V_{FM}	1		1.3	1.7	V	
Max. instantaneous reverse current at rated DC blocking voltage	I_{RM}	5					μA
		100					
Operating junction temperature	T_J	-55 ~ +150					°C
Storage temperature	T_{STG}	-55 ~ +150					°C
Maximum reverse recovery time (Note1)	t_{rr}	35					nS
Typical thermal resistance (Note2)	R_{J-C}	32					°C/W
	R_{J-A}	66					°C/W

Notes:

1 Reverse Recovery Test Conditions: $I_F=0.5A$, $I_R=1.0A$, $IRR=0.25A$

2 The thermal resistance from junction to ambient, case or mount, mounted on P.C.B with 8x8mm copper pads, 2 OZ, FR4 PCB

Ordering information (Example)

PREFERRED	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
FU1				

Typical characteristics




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Reverse Characteristics







Figure 4. Typical Instantaneous Forward Characteristics


Package outline dimensions

in inches (millimeters)



DIM	Unit: mm		Unit: inch	
	MIN	MAX	MIN	MAX
A	0.9	1.08	0.035	0.043
A1	0	0.1	0.000	0.004
B	0.85	1.05	0.033	0.041
C	0.1	0.25	0.004	0.010
D	1.7	2	0.067	0.079
E	2.9	3.1	0.114	0.122
L	0.43	0.83	0.017	0.033
HE	3.5	3.9	0.138	0.154

Soldering footprint



Golden SEMI Inc. - Legal Notice

Disclaimer – All data and specifications are subject to changes without notice

GOLDEN SEMI Inc, it's affiliates, agents, distributors and employees neither accept nor assume any responsibility for errors or inaccuracies. All data and specifications are intended for information and provide a product description only. Electrical and mechanical parameters listed in GOLDEN SEMI data sheets and specifications will vary dependent upon application and environmental conditions . GOLDEN SEMI is not liable for any damages occurred or resulting from any circuit, product or end-use application for which it's products are used. GOLDEN SEMI products are not intended or designed for use in life saving or sustaining apparatus and purchase of any GOLDEN SEMI products automatically indemnifies GOLDEN SEMI against any claims or damages resulting from application malfunction